

**Suttner foam guns**

**ST-3100**



Professional gun with progressive closing system. Gun with coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 60 bar / 100 l/min / 150 °C

<b>R+M Nr.</b>		
203 100 805	coupling ST-3100	1/2" F swivel



Professional gun with progressive closing system. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 60 bar / 100 l/min / 150 °C

<b>R+M Nr.</b>		
203 100 840	3/8" F	1/2" F



Professional gun with progressive closing system. Gun with coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 60 bar / 100 l/min / 150 °C

<b>R+M Nr.</b>		
203 100 810	coupling ST-3100	1/2" F

**ST-3100**



Professional gun with progressive closing system. Gun with coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 60 bar / 100 l/min / 150 °C

<b>R+M Nr.</b>		
203 100 820	coupling ST-3100	1/2" F

**ST-340**



1/2" M : 1/2" F

<b>R+M Nr.</b>
200 340 010



Repair kit ST-340

<b>R+M Nr.</b>
200 340 100

**ST-3100**



Seal kit

<b>R+M Nr.</b>
203 100 400

**ST-3300**



Seal kit

<b>R+M Nr.</b>
203 300 490

**ST-3300**



Professional high-flow gun. Gun with coupling ST-45. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Max. 150 bar / 100 l/min / 150 °C

<b>R+M Nr.</b>		
203 300 500	coupling ST-45	1/2" F



Professional high-flow gun. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Max. 150 bar / 100 l/min / 150 °C

<b>R+M Nr.</b>		
203 300 510	1/2" F	1/2" F

**Lance holder**



Stainless steel. Wall mount for 5 lances

<b>R+M Nr.</b>
040 003 830

**Symbols** length inlet outlet insulation material nozzle weight colour