

## Suttner foam guns, ST-3225



**LTF**  
Professional hp gun with progressive closing system and coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 60 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 550	coupling ST-3100	1/2" F swivel



**LTF**  
Professional hp gun with progressive closing system. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 60 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 545	1/2" F	1/2" F swivel



**LTF**  
Professional hp gun with coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 60 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 540	coupling ST-3100	1/2" F swivel



**LTF**  
Professional gun with progressive closing system, locking in opened position and coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 24.5 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 650	coupling ST-3100	1/2" F swivel



**LTF**  
Professional gun with progressive closing system and locking in opened position. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 24.5 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 645	1/2" F	1/2" F swivel



**LTF**  
Professional gun with locking in opened position and coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 24.5 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 640	coupling ST-3100	1/2" F swivel

## Foam lances

### ST-74 foam lances with air injector



1/4" F. Foam lance stainless steel with air injector and stainless steel socket with nozzle 40° 150. Max. 90 °C

R+M Nr.	D	air injector	⊖	M	↔
200 074 505	2.1 mm		0.8 kg	stainless steel	530 mm
200 074 500	2.3 mm		0.8 kg	stainless steel	530 mm


### Foam lance ST-3100



Plug ST-3100. Foam lance stainless steel 300 mm with foam nozzle 50° 200

R+M Nr.	D	ISO	M	↔
203 100 630	50° 200	-	stainless steel	300 mm

## Nozzle protector ST-11



- » The nozzle protector ST-11 is suitable for nozzles 1/4" M.
- » Made out of plastics intended to come into contact with foodstuffs according to Regulation (EC) No. 1935/2004.
- » It is clamped undetachably between the nozzle and the nozzle sleeve.

R+M Nr.	C
020 001 124	white
020 001 149	blue
020 001 121	red
020 001 122	green

R+M Nr.	C
020 001 123	yellow
020 001 157	grey
020 001 158	black