

## Foam lances

### Lances with female thread



1/4" M. Lance with moulded handle Cool & Compact. Comfortable grip and ergonomic shape. Heat-proof insulation. Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	☹	M	R+M Nr.
200 129 140	1/4" F BSP	300 mm	500 mm	stainless steel	
200 129 145	1/4" F BSP	400 mm	700 mm	stainless steel	
200 129 150	1/4" F BSP	400 mm	800 mm	stainless steel	



1/4" M. Lance. Max. 400 bar / 150 °C

R+M Nr.	☺	☹	M	R+M Nr.
070 000 097	1/4" F BSP	100 mm	stainless steel	
070 000 098	1/4" F BSP	150 mm	stainless steel	
070 000 099	1/4" F BSP	200 mm	stainless steel	
070 000 095	1/4" F BSP	250 mm	stainless steel	
070 000 101	1/4" F BSP	350 mm	stainless steel	

## Rubber protected ball valves



Stainless steel.  
Max. 60 bar / 95 °C

R+M Nr.	☺	☹
500 155	1/2" F	ST-3100



Stainless steel.  
Max. 60 bar / 95 °C

R+M Nr.	☺	☹
500 150	1/2" F	1/2" F



Stainless steel.  
Max. 60 bar / 95 °C

R+M Nr.	☺	☹
500 160	1/2" F	1/2" F



ST-3100. Stainless steel.  
Max. 60 bar / 95 °C

R+M Nr.	☺	☹
203 100 250	1/2" F	1/2" F



ST-3100. Stainless steel.  
Max. 60 bar / 95 °C

R+M Nr.	☺	☹
203 100 260	1/2" F	ST-3100

## Ball valves



Ball valve with safety guard. Stainless steel.  
Max. 140 bar / 80 °C

R+M Nr.	☺	☹
203 100 200	1/2" F	ST-3100



Ball valve with safety guard. Stainless steel.  
Max. 140 bar / 80 °C

R+M Nr.	☺	☹
203 100 210	ST-3100	ST-3100