

Suttner foam injectors

ST-60.1



Coupling ST-45-250 : plug ST-45-250. Injector with metering valve, suction hose 1,000 mm and suction filter ST-31. Max. 250 bar / 60 °C

R+M Nr.	⌀	h
200 060 750	1.6 mm	

ST-60.1



Injector without metering valve. Max. 250 bar / 60 °C

R+M Nr.	⌀	h	⌀	D
200 060 700	3/8" M	3/8" F	1.6 mm	
200 060 710	3/8" M	3/8" F	1.8 mm	

ST-60.1



M22 F : M22 M. Injector with metering valve, suction hose 1,000 mm and suction filter ST-31. Max. 250 bar / 60 °C

R+M Nr.	⌀	h
200 060 760	1.6 mm	

Metering valves



Valve for Suttner injector. Hose tail 6 mm

R+M Nr.
050 000 370 1
200 061 500 2

Repair kits



Chemical check valve. Hose tail 6 mm

R+M Nr.
200 060 725

The suitable foam lances are presented on pages 321- 330.

Intake filter for chemicals



DN 6 mm. ST-32. Brass

R+M Nr.	⌀	h
200 032 800	20	32



DN 6 - 8 mm. ST-32. Stainless steel

R+M Nr.	⌀	h
200 032 600	19	39



DN 6 - 8 mm. ST-31 without check valve. Plastic. Brass weight

R+M Nr.	⌀	h
200 031 600	20	75



DN 6 - 8 mm. ST-31 without check valve. Plastic. Stainless steel weight

R+M Nr.	⌀	h
200 031 615	20	75



DN 6 - 8 mm. ST-31R with check valve. Plastic. Brass weight

R+M Nr.	⌀	h
200 031 610	20	75



DN 6 - 8 mm. ST-31R with check valve. Plastic. Stainless steel weight

R+M Nr.	⌀	h
200 031 611	20	75

Symbols outlet inlet nozzle **DN** nominal diameter **TYP** type height diameter flow