

Wash brushes



A= 260. B= 230 x 80 mm. Hog hair. Max. 50 °C

A= 260. B= 230 x 80 mm. Hog hair. Max. 50 °C

A= 260. B= 230 x 80 mm. Hog hair. With stainless steel frame. Max. 50 °C

A= 260. B= 230 x 80 mm. Hog hair. Max. 50 °C

R+M Nr.	C	Ⓢ
523 703	60 mm	1/8" M

R+M Nr.	C	Ⓢ
200 023 700	60 mm	1/4" F

R+M Nr.	C	Ⓢ
200 023 730	60 mm	1/4" F

R+M Nr.	C	Ⓢ
523 701	60 mm	M18 x 1.5 F

The original

Vorwerk lances & wash brushes



Extension pipe with water flow

R+M Nr.	↔	Ⓢ	Ⓢ
523 790 1	1,000 mm	1/4" M	1/4" F
523 790 2	1,500 mm	1/4" M	1/4" F
523 790 3	2,000 mm	1/4" M	1/4" F

Vorwerk wash brushes



A= 300. B= 300 x 100 mm. Nylon

R+M Nr.	C	Ⓢ
523 780	60 mm	1/4" F



A= 240. B= 230 x 80 mm. Hog hair

R+M Nr.	C	Ⓢ
523 70	60 mm	1/4" F
523 75	90 mm	1/4" F

Adaptor



Adaptor for lances with coarse thread.

Coarse thread : 1/4" M

R+M Nr.
010 003 610



Brush. A= 260. B= 230 x 80 mm. Hog hair

R+M Nr.	C
523 72	60 mm
523 73	90 mm



Frame. 260 mm. Aluminium

R+M Nr.	Ⓢ
523 76	1/4" F

Air injector



1/4" F : 1/4" M. Flow at 100 bar

R+M Nr.	↔	∅
108 290 60	13 l/min	1.5
108 290 20	34 l/min	2.5

Symbols ↔ length Ⓢ inlet Ⓢ outlet ∅ diameter TYP type P pressure ↔ flow ISO insulation M material