

Vacuum tools

Grout nozzles



R+M Nr.	↔	∅
263 219	200 mm	32 mm



R+M Nr.	↔	∅
263 619	200 mm	35 mm
263 619 1	300 mm	35 mm
263 619 2	370 mm	35 mm



R+M Nr.	↔	∅
264 020	305 mm	38 mm



R+M Nr.	↔	∅
264 019	245 mm	45 mm



R+M Nr.	↔	∅
264 019 3	350 mm	45 mm



R+M Nr.	↔	∅
264 019 4	350 mm	45 mm



R+M Nr.	↔	∅
265 018	270 mm	58 mm



Glass fibre reinforced

R+M Nr.	↔	∅
265 019	230 mm	58 mm

R+M Nr.	↔	∅
265 022 1	370 mm	58 mm



R+M Nr.	↔	∅
265 020	370 mm	58 mm



R+M Nr.	↔	∅
265 022	370 mm	58 mm



Flexible grout nozzles



Rotating. Anti-theft protection due to three-part clip locking system

R+M Nr.	↔	∅
264 019 12	375 mm	DN 38



Rotating. Anti-theft protection due to three-part clip locking system

R+M Nr.	↔	∅
264 019 13	375 mm	DN 38



Rotating. Easy assembly due to screw thread

R+M Nr.	↔	∅
264 019 1	420 mm	DN 38



With inner bar 18 cm. Rotating. Rotating. Easy assembly due to screw thread

R+M Nr.	↔	∅
264 019 11	420 mm	DN 38



Rotating. Easy assembly due to screw thread

R+M Nr.	↔	∅
265 019 1	420 mm	DN 50



With inner bar 18 cm. Rotating. Easy assembly due to screw thread

R+M Nr.	↔	∅
265 019 11	420 mm	DN 50



Flexible. PVC

R+M Nr.	↔	∅
263 621	630 mm	35 mm