


Motorschutzschalter

Typ OKN




Gehäuse für Typ OKN

| R+M Nr. | Schaltbereich |
|---------|---------------|
| 901 516 | 10,0 - 16,0 A |
| 901 522 | 16,0 - 22,0 A |
| 901 527 | 22,0 - 27,0 A |

| R+M Nr. | M |
|---------|------------|
| 901 540 | Kunststoff |

Betriebsstundenzähler




Zähler mit Klemme

| R+M Nr. | V |
|-----------|---------|
| 915 102 4 | 24 V ~ |
| 915 122 0 | 230 V ~ |
| 915 140 0 | 400 V ~ |

Thermometer

Thermometer mit Fernkontakt einstellbar


Typ WIMEX



Gehäuse für Typ WIMEX, IP55

| R+M Nr. | Schaltbereich |
|---------|---------------|
| 901 710 | 6,3 - 10,0 A |
| 901 716 | 10,0 - 16,0 A |
| 901 720 | 16,0 - 20,0 A |
| 901 725 | 20,0 - 25,0 A |

| R+M Nr. | M |
|---------|------------|
| 901 730 | Kunststoff |





1/2" AG. Kontakt 5 A - 250 V (AC1).
Temperaturanzeige 0 - 120 °C

| R+M Nr. | Schaltbereich | Kapillarrohr |
|---------|---------------|--------------|
| 910 20 | 0 - 80 °C | 1.000 mm |

Thermostate



Emerson 1536



M14 x 1 AG. Kontakt 16 A - 380 V (AC1)

| R+M Nr. | Schaltbereich | Kapillarrohr |
|---------|---------------|--------------|
| 910 16 | 0 - 160 °C | 1.550 mm |


Fühler mit Verschraubung



3/8" AG. Kontakt 16 A - 380 V (AC1)

| R+M Nr. | Schaltbereich | Kapillarrohr |
|---------|---------------|--------------|
| 910 12 | 30 - 150 °C | 1.520 mm |
| 910 13 | 0 - 152 °C | 920 mm |

Emerson 8654



3/8" AG. Kontakt 16 A - 380 V (AC1)

| R+M Nr. | Schaltbereich | Kapillarrohr |
|---------|---------------|--------------|
| 910 15 | 30 - 150 °C | 1.550 mm |